



NOTES:

ELECTRICAL:

- 1. Contact Resistance : 20MΩ MAX
- 2. Insulation Resistance : 500MΩ MIN @ 500V DC
- 3. Withstand Voltage : DC1000V AC700V RMS 60Hz, 1MIN
- 4. CAT. 6A PERMANENT LINK : CONFORM TO ANSI/TIA/EIA 568C.2  
ISO 11801:2010 CLASS EA

ENVIRONMENTAL:

- 1. Storage : -40° TO+70°
- 2. Operation : -10° to+60°

MECHANICAL

- 1. SHIELD MATERIAL: ZINC ALLOY
- 2. IDC MATERIAL: PC UL94V0 TERMINAL:PHOSPHOR BRONZE, TIN PLATING
- 3. RJ45 Contact Life: 750 Times Min
- 4. IDC Life : 250 Times Min
- 5. RJ45 DIMENSION:11.9MM\*9.8MM
- 6. WEIGHT: 34.7G

TYPE

- 1. SHIELDED CAT. 6A KEYSTONE JACK
- 2. COLOUR:SILVERY WHITE

Accessory:

Cable Tie(75X1.9mm)×2Pcs

RoHS 2.0 & REACH Compliant

MATERIAL LIST:

⑦	MODULAR COVER	FIREPROOF PC UL94V0	1	
⑥	RJ 45 JACK INSERT	8P8C 3U" GOLD PLATED	8	
⑤	PCB	1.6mm UL 94V0	1	
④	IDC BODY	FIREPROOF/PC UL 94V0	1	
③	IDC PIN	PHOSPHOR BRONZE & TINNED	8	
②	LABEL COLOR CODE	T568A/B	2	
①	IDC TERMINAL	FOR 22-26AWG CABLE	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK

					PRODUCT NAME	CAT. 6A STP KEYSTONE JACK		UNIT	MM
				A	DRAWNBY	CHECKBY	APPOBY	DATE	
BY	CHK		DATE	REV.					